



Revised 3/05/18

Contact:

Division Head Official

Mike Mansch

916-761-2076

freeportautomotive@sbcglobal.net

Head Tech Official

Gary Quigley

916-303-0060

gquigley@rpmnorcal.com

DOC

Frank Jordan

916-997-6080

fjordan@bmrnapa.com

Late Model Series 2018

Working with Kenny Shepherd at Madera Speedway and the successful programs he has constructed in the Late Model and Jr. Late Model Series BMRP is implementing the rules of these popular divisions. We will include both at All American Speedway to assist with the growth of what has always been a competitor favorite.

All American Speedway/BMRP reserves the rights to alter or change rules at any time for competitor safety, affordability, or to keep competition fair. There will be a memorandum communicating any needed changes to competitors.

Late Model Series Rules

1. Any late model type chassis allowed / Body type is open. There is a 48" maximum front overhang measured from the axle measured to the forward most part of the car, ABC nose piece firmly recommended (note, any car that does not run an ABC style nose will be on a zero-contact policy). There is a 55" maximum rear overhang measured from the rear axle to the rearward most part of the race car body/bumper/spoiler (nothing may extend beyond 55"). Note; If the rear bumper rail is exposed, it must be rounded where it meets the quarter panels so that it has no square edges and it must turn back in behind the rear tires and connect to back to the frame. The bumper must extend to the rear of the car even with the spoiler or extend beyond the spoiler of the car. Maximum rear quarter panel height is 36 ". Maximum rear width of the body at bumper height across the rear of the car is 72". The window opening on the driver's side must be a minimum of 13" at the center of the door to the roof. Minimum wheel base is 101". Ride height rule; all cars must be able to get on and off the inspection scales without the use of any extra ramps or boards and the car must not drag on the scales.

2. Any cast iron block wet sump engine allowed. The only rule on the open engine is that it must be a wet sump engine with only a single 4bbl carburetor allowed. The open engine car weight is 3075lbs and a maximum of 58% left side weight.

The CT525 crate engine with an aluminum block will be allowed and will be the only aluminum block allowed. The CT525 will be treated as an open engine at the 3075lb weight with a maximum of 58% left side weight, the engine set back is 2" to the center of the forward most spark plug to the center of the upper ball joint on the same side and left side weight for the CT525 is 58%, all CT525 cars must bolt 40 pounds of weight to the front clip (20 pounds on each side after the kick up just behind the front cross member). CT525 cars may also bolt the 40 pounds to the engine block via a weight belt. CT525 cars must run a 6,800 RPM MSD rev chip. Any single 4bbl carburetor allowed.

3. The engine set-back rule is 2" back for all open engines (the center of the forward most spark plug hole to the center of the upper ball joint on the same side). Maximum engine set-back for the 602 crate engine is 6" measured the same way.



Revised 3/05/18

4. 602 crate engine cars are to be a minimum of 2875lbs total weight and a maximum of 60% left side weight. All other open cast iron block engines are to be 3075lbs and a maximum of 58% left side weight. 602 engines must remain OEM from factory and may not turn more than 6,200 RPM's.
5. Any single 4bbl carburetor allowed.
6. Tires are the Hoosier 8.0-15/970 treaded tire. ALL tires MUST be purchased from All American Speedway approved tire vendor, and tires MAY NOT be cut, soaked or altered in any way. Any team wishing to run used tires must submit the tires for inspection and scanning prior to qualifying, note these used tires must have been purchased from All American Speedway.
7. Wheels must be steel and not exceed 8" in width.
8. Competitors must start the race on the tires they qualified with.
9. Any steel shock, all external parts must be steel (Aluminum rod end on the shaft end ok, and an aluminum thread in body cap on the shaft end is ok)
10. No traction control devices.
11. All competing cars will not exceed 79" inch track width, it will be measured from the bulge outside to outside of the front tires at the spindle height. No independent rear suspension.
12. Rear Spoiler may be no wider than 60", and no taller than 6 1/2". There may be NO forward support of any kind, no boxed ends or runners. No Gurney lip, or any type of wicker bill on the upper edge of the spoiler. It is highly, highly recommended that the Upper 2/3's of the spoiler and the rear window of the car be made of "clear" lexan to enable other drivers to see through them.
13. DRY SUMP ENGINE CARS- You may run a steel engine block tour legal car with a dry sump engine in the Pro Late Model series. Track width must not exceed 75" it will be measured from the bulge outside to outside of the front tires at the spindle height. Must use an all steel shock (aluminum rod end on shaft end ok, aluminum coil over kit ok). Left side weight not to exceed 58%, minimum weight is 3,075 pounds prior to race and qualifying. Must use 8" steel wheel and the Hoosier 8.0-15/970 treaded tire.
14. All cars must run the track spec fuel, the track spec fuel is Sunoco 110 Purple race fuel or Sunoco E-85R race fuel. Teams may also run stock Chevron 91 octane pump fuel with NO additives and NO mixing of fuels.
15. Drive shaft, NO carbon fiber drive shafts allowed.

Note, the following infractions will result in a firm penalty which could include a LIFETIME ban from the series.

- A. Being caught with traction control.
- B. Bypassing the RPM limiting control device in any way.
- C. Altering the 602 crate engine under the seals in any way that is non OEM. (you may run aftermarket valve springs but they must be the same spring pressures as OEM, you may run any carburetor, you may run the approved aftermarket replacement distributor, you must run a mechanical fuel pump in the stock location, and you must run the stock oil pan and stock harmonic balancer).
- D. Altering the Hoosier 970 tire, such as soaking the tire, or cutting the tire. Tires are to be a stock 970 tire.
- E. If you are caught cheating the fuel in any way, the fuel must be stock as provided by the manufacturer and must not have ANY additives whatsoever.

Illegal components WILL be confiscated by All American Speedway and become property of the speedway.